D12/STRONG WRAP: FR SCAFFOLD WRAP

Product Features:

- Fire-Retardant: Meets NFPA 701 Method II & Boston Fire Marshal Test BFD IX-1
- Premium Quality String Reinforced Poly
- Base Material:

3 x 3 Weave Per Square Inch, 2400 Denier 250 GSM Including Reinforcing Band

Color: Milky White

Reinforced Bands:

14 × 14 Weave Per Square Inch, 1200 Denier Pre-Punched 15mm Eyelets For Easy Installation

Color: Gray

- Easy To Install & Remove With Strong Man Bungee Cords
- Superior Performance In Cold & Extreme Weather Conditions
- UV-Treated & Highly Rip-Resistant

Product Uses:

- Scaffold & Building Enclosure
- Total Weather & Jobsite Protection
- Abatement, Demolition & Restoration Enclosure
- Debris, Dust, Paint Overspray & Sandblast Containment
- Temporary Heat Enclosure
- Ideal For Use On Scaffold, Bridges, Towers & Tall Buildings

Availability		
Sizes	with 3 Bands	with 5 Bands
7'6" x 100'	✓	
8'6" x 100'	✓	
13' x 100'		/



Use With Our BC-111 Bungee Cords & HD Poly **Tape To Ensure Proper Installation!**

